



产

R RK3588J S C 2.0 GH
4 C -76 + 4 C -A55 + 6 TOPS NPU
8/16GB LPDDR5 + 32/64/128GB MMC
1 HDMI 2.0
2 RJ45, 4 USB
ROS2/U 22.04
-20 60

		R RK3588J
	CPU	ARM C -A76 + ARM C -A55, 2.0GH
	NPU	6 TOPS N N
		G (4 PCIE M.2), DRAM(2.5GB/5GB)
		8/16GB LPDDR5
		32/64/128GB MMC 5.1 OS 1 M.2 2280 SSD RJ45 1 M.2 2280 (PCIE 4) 1
	GPU	A M -G610 MP4, O GL ES 1.1/2.0/3.2, O CL 2.2,
		H.265, VP9, AVS2 , 8K60; H.265, H.264 , 8K30
		1 M.2 K E /BT
	4G/5G	1 M.2 K B 4G/5G
I/O	I/O	1 P ,1 R ,1 SSD L ,1 P L 1 HDMI 1 SIM
	I/O	1 DC IN 1 USB 3.0 T -C OTG 3 USB 3.0 T -A 2 RJ45,10/100/1000 M
		130 125 50
		9 36V
		ROS2, U 22.04
		-20 60
		-40 85
		10% 90% ,



				LAN	USB	SSD	
EII-2000-AOH00	RK3588J	16GB	64GB	2	4	1	-20 60
EII-2000-AOM00	RK3588J	8GB	32GB	2	4	1	-20 60
EII-2000-BOH00	RK3588	16GB	64GB	2	4	1	0 60
EII-2000-BOM00	RK3588	8GB	32GB	2	4	1	0 60



60	AC 100 240V DC 12V @5A, 5.5 2.5



SSD128GB	SSD128GB,M.2 M-KE ,2280		
SSD256GB	SSD256GB,M.2 M-KE ,2280		
4G/5GM	4G/5GM	A	
F & B M	F & B	M	A